



HS48 SERIES 45° SERRATION

Nom. Dia.	Dec. Equiv.	OD	Length	Bore	Whole Depth	Specify Class A, B, C, D
1/2	.500	3/4	1/2	8mm	.014	HS48-050M
1/2	.500	1-1/4	1-1/4	1/2	.014	HS48-050H
1/2	.500	1-7/8	1-1/2	3/4	.014	HS48-050S
5/8	.625	1-7/8	1-1/2	3/4	.017	HS48-062S
3/4	.750	1-1/4	1-1/4	1/2	.018	HS48-075H
3/4	.750	1-7/8	1-1/2	3/4	.018	HS48-075S
3/4	.750	2-1/2	2	1-1/4	.018	HS48-075
7/8	.875	1-1/4	1-1/4	1/2	.021	HS48-087H
7/8	.875	1-7/8	1-1/2	3/4	.021	HS48-087S
7/8	.875	2-1/2	2	1-1/4	.021	HS48-087
1	1.0	1-1/4	1-1/4	1/2	.0265	HS48-100H
1	1.0	1-7/8	1-1/2	3/4	.0265	HS48-100S
1	1.0	2-1/2	2	1-1/4	.0265	HS48-100
1-1/8	1.125	1-1/4	1-1/4	1/2	.029	HS48-112H
1-1/8	1.125	1-7/8	1-1/2	3/4	.029	HS48-112S
1-1/8	1.125	2-1/2	2	1-1/4	.029	HS48-112
1-1/4	1.250	1-1/4	1-1/4	1/2	.0325	HS48-125H
1-1/4	1.250	1-7/8	1-1/2	3/4	.0325	HS48-125S
1-1/4	1.250	2-1/2	2	1-1/4	.0325	HS48-125
1-3/8	1.375	1-1/4	1-1/4	1/2	.035	HS48-137H
1-3/8	1.375	1-7/8	1-1/2	3/4	.035	HS48-137S
1-3/8	1.375	2-1/2	2	1-1/4	.035	HS48-137
1-1/2	1.5	1-1/4	1-1/4	1/2	.0385	HS48-150H
1-1/2	1.5	1-7/8	1-1/2	3/4	.0385	HS48-150S
1-1/2	1.5	2-1/2	2	1-1/4	.0385	HS48-150
1-3/4	1.75	1-1/4	1-1/4	1/2	.044	HS48-175H
1-3/4	1.75	1-7/8	1-1/2	3/4	.044	HS48-175S
1-3/4	1.75	2-1/2	2	1-1/4	.044	HS48-175
2	2.0	1-1/4	1-1/4	1/2	.050	HS48-200H
2	2.0	1-7/8	1-1/2	3/4	.050	HS48-200S
2	2.0	2-1/2	2	1-1/4	.050	HS48-200
2-1/4	2.25	1-7/8	1-1/2	3/4	.056	HS48-225S
2-1/4	2.25	2-1/2	2	1-1/4	.056	HS48-225
2-1/2	2.5	1-7/8	1-1/2	3/4	.062	HS48-250S
2-1/2	2.5	2-1/2	2	1-1/4	.062	HS48-250

48-T SAE Straight Sided Single Thread, Right Hand Non-Topping



Multi-start 48 serration hobs are a new product line. Some hobs may require back order.

Multi-lead hob available, please inquire.

**Premium Steel
PM M45 & M42 In Stock!!**

DON'T SEE WHAT YOU WANT?

Sizes and configurations shown are the most popular. Other sizes and configurations available from stock, please call.