



DIN 5462 & 5463 UNI 220

HX8 SERIES

8 Spline Parallel Sides, Finishing, Single Thread Right Hand, Lugs, Chamfering

Will Produce			Hob Size			Specify Class B, C, D
Major Dia.	Root Dia.	Key	OD	Length	Bore	
36mm (1.417")	32mm (1.260")	6mm (.236")	2-3/4	2-3/4	1-1/4	HX8-36-32
38mm (1.496")	32mm (1.260")	6mm (.236")	2-3/4	2-3/4	1-1/4	HX8-38-32
40mm (1.575")	36mm (1.417")	7mm (.276")	2-3/4	2-3/4	1-1/4	HX8-40-36
42mm (1.654")	36mm (1.417")	7mm (.276")	2-3/4	2-3/4	1-1/4	HX8-42-36
46mm (1.811")	42mm (1.654")	8mm (.315")	3	3	1-1/4	HX8-46-42
48mm (1.890")	42mm (1.654")	8mm (.315")	3	3	1-1/4	HX8-48-42
50mm (1.969")	46mm (1.811")	9mm (.354")	3	3	1-1/4	HX8-50-46
54mm (2.126")	46mm (1.811")	9mm (.354")	3-1/4	3	1-1/4	HX8-54-46
58mm (2.283")	52mm (2.047")	10mm (.394")	3-1/4	3	1-1/4	HX8-58-52
60mm (2.362")	52mm (2.047")	10mm (.394")	3-1/4	3	1-1/4	HX8-60-52
62mm (2.441")	56mm (2.205")	10mm (.394")	3-1/4	3	1-1/4	HX8-62-56
65mm (2.559")	56mm (2.205")	10mm (.394")	3-1/2	3-1/2	1-1/4	HX8-65-56
68mm (2.677")	62mm (2.441")	12mm (.472")	3-1/2	3-1/2	1-1/4	HX8-68-62
72mm (2.835")	62mm (2.441")	12mm (.472")	3-1/2	3-1/2	1-1/4	HX8-72-62